

# GENSET MODEL PPG60

| POWERPAC             | PERKINS      | 380-415 50hz |          | 480v 60hz |    |
|----------------------|--------------|--------------|----------|-----------|----|
| Generating Set Model | Engine Model | KVA          | KW       | KVA       | KW |
| PPG60 (Prime)        | 1103A-33TG2  | 60           | 48       | 65        | 52 |
| PPG60 (Standby)      | 1103A-33TG2  | 66           | 52.8     | 72.5      | 58 |
| ALTERNATOR MODELS    |              |              |          |           |    |
| Newage Stamford      | Mecc Alte    | Leroy Somer  |          |           |    |
| UCI224E              | ECO32-1L     | LSA43.2 S25  |          |           |    |
| CONTROL PANEL        |              |              |          |           |    |
| DEEPSEA              |              |              | SMARTGEN |           |    |
| DSE4520              |              |              | HGM420N  |           |    |

## RATINGS:


- Prime Output:**  
 This rating is applicable for supplying continuous electrical power at variable load. There is no limitation to the annual hours of operation and this model can supply 10% overload power for one hour in 12 hours.
- Standby Output:**  
 This rating is applicable for supplying electrical power (at variables load) in the event of a utility power failure. No overload is permitted on these ratings.
- Standard References Conditions:**  
 25°C, 100ml A.S.L, 30% relative humidity.

## Design Features:

- High Quality assembly, providing stiffness and low vibration.
- Powder coated steel, Corrosion and scratch resistant.
- Compact and long service life.
- Wiring and connectors with double protection.
- Protection guards in radiator and high voltage parts.
- Full 12 month Warranty.

## Design Standards:

- CE marking
- ISO8528-1995
- GB/T2820-1997
- ISO 9001:2008 Registered Company



## CONFIGURATION:

- 4-Stroke water-cooled diesel engine
- Industrial silencer
- Coolant recovery tank
- Single bearing, 4 pole brushless alternator
- Anti vibration mounting
- Integral fuel tank with fully bounded base protection
- Fuel level sensor
- Control Panel - DEEPSEA/SMARTGEN
- Auto start control system with electronic digital control module DSE6020 as standard
- Output circuit breaker
- Emergency stop button
- High engine temprature and low oil pressure shutdown system
- 12V starter battery with leads and switch

## TROLLY:

- 4 Wheel Trolley Mounted
- Steerable
- Towable
- Having Brake

## AUCOUSTIC CANAOPY FEATURES:

- Water and dust proof design
- Door locks
- High quality sound absorbing and fire retardant inner material
- Lifting lugs
- Forklift holes in base